M550 Tile Grout





M550 is a high quality cement based tile grout with special components such as high bond adhesive, anti-crack, reducing water absorbance, anti-fungus and easy to clean. It can be applied immediately after mixed with clean water at the recommended ratio.

Instruction of preparation and application

Surface preparation

Before grouting, clean the surface and joint until free from dirt, oil, water, dust and any particles and contaminates which can effect to the bond adhesion.

Mixing

Mix 1 kg of TPI M550 with 0.3 liters of clean water until the mixture is homogenous.


Grouting


Fill the mixture between the tiles 'joint by using with rubber trowel to swipe and press diagonally to be smooth. Wait until it is almost dried then clean off the excess grout on the tile surface.

Typical Data

Approximately usage area 5 m^2 per 1kg and the recommended joint width is 1-6 mm.

Tile's size (inch)	Area of work (square meter)
24 x 24	8 - 10
12 x 12	6 - 8
8 x 8	4 - 5
4 x 4	3 - 4





- Pearl white
- Gray white
- Natural
- Midnight gray
- Cloth cream
- Light yellow
- New gamboge
- Pink lady
- Allzarin crimson
- Honey brown
- Winsor red
- Cocoa
- Burnt sienna
- Peppermint
- Green potpourri
- Cobalt turquoise
- Blue
- Cobalt blue
- Amethyst
- Mauve

Suitable for Grouting on Gaps between Tiles with more High Adhesive, Less Crack and Anti Fungus.