FINE FISSURED™ Second Look®

Scored Tegular
medium texture

GREENGUARD Gold Certified
(details below)

UP TO 56% RECYCLED CONTENT

Calculate LEED contribution at armstrongceilings.com/greengenie

LEED® energy management ✓ | construction waste mgmt ✓ | regional materials ✓ | design for flexibility ✓ | EPD | recyclable/ extended producer resp. ✓ | biobased materials ✓ | recycled content ✓ | sourcing of raw materials ✓ | material ingredient reporting ✓ | low emitting/ materials ✓ | lighting quality ✓ | acoustics ✓

▲ LOCATION DEPENDENT

$$$$



Fine Fissured™ Second Look® II panels with Suprafine® XL® 9/16" suspension system (Pgs. 466-467)

This panel offers economical, standard acoustics and scored visuals.

KEY SELECTION ATTRIBUTES

- Geometric scored visuals
- Economical option to create a designer look
- 10-Year replacement panel available for items 1761

10-YEAR REPLACEMENT PANEL AVAILABILITY

COLOR

White (WH)

FACE VIEW

Second Look I

Second Look II



Second Look III

VISUAL SELECTION

Edge Profile	Susp. Dwg. Pgs. 474-478 armstrongceilings.com/catdwgs	Item No.	Dimensions (Inches)	
FINE FISSURED™ Second Look®				
15/16" Angled Tegular	11	**1760**	24 x 48 x 3/4"	Second Look I
	11	**1761**	24 x 48 x 3/4"	Second Look II
	11	**1861**	24 x 48 x 3/4"	Second Look II
	11	**1762**	24 x 48 x 3/4"	Second Look III
9/16" Angled Tegular	27	**1765**	24 x 48 x 3/4"	Second Look I
	27	**1766**	24 x 48 x 3/4"	Second Look II

PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics NRC	+ CAC	= Total Acoustics[1]	Fire Performance	Light Reflect	Mold & Mildew Protection: Bio-Block	Mold & Mildew Protection: Humi-Guard+	Sag Resist	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	30-yr Warranty
0.55	35 •	–	Class A	0.84 •	•	•	•		Std	Std	•	•
0.55	35 •	–	Class A	0.84 •	•	•	•		Std	Std	•	•
0.55	35 •	–	Fire Guard™	0.84 •	•	•	•		Std	Std	•	•
0.50	35 •	–	Class A	0.84 •	•	•	•		Std	Std	•	•
0.55	30	–	Class A	0.84 •	•	•	•		Std	Std	•	•
0.55	30	–	Class A	0.84 •	•	•	•		Std	Std	•	•

[1] Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.

SUSPENSION SYSTEMS

15/16" Prelude® Prelude® XL® Fire Guard™

9/16" Suprafine®

PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled). Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies (Class A).

ASTM E1264 Classification
Type III, Form 2, Pattern C E K
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

VOC Emissions
GREENGUARD Gold Certified
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

GREENGUARD GOLD

Insulation Value
R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong® suspension system. Details at armstrongceilings.com

Design Consideration
Do not mix Fine Fissured™ Second Look® panels with standard Fine Fissured panels in the same room.

Weight; Square Feet/Carton
0.75 lbs/SF; 80 SF/ctn

Minimum Order Quantity
1 carton

Metric Items Available
1761M - Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

TechLine / 1 877 276-7876
armstrongceilings.com/commercial
(search: fine fissured)
BPCS-3027-718

LEED® is a registered trademark of the U.S. Green Building Council
UL is a registered trademark of UL LLC. All other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates
© 2018 AWI Licensing LLC Printed in the United States of America

Armstrong® CEILING & WALL SOLUTIONS

FISSURED™

Square Lay-in & Tegular
medium texture

GREENGUARD Gold Certified (details below)

UP TO 41% RECYCLED CONTENT

Calculate LEED contribution at armstrongceilings.com/greengenie

LEED®: energy management ✓ | construction waste mgmt ✓ | regional materials ✓ | design for flexibility ✓ | EPD ● | recyclable/extended producer resp. ✓ | biobased materials ✓ | recycled content ✓ | sourcing of raw materials ✓ | material ingredient reporting ● | low emitting/materials ✓ | lighting quality ✓ | acoustics ✓

▲ LOCATION DEPENDENT

$$$$



Fissured™ Angled Tegular panels with Prelude® XL® 15/16" suspension system (Pgs. 458-459)

This economical panel with a directional, fissured visual offers standard acoustics.

KEY SELECTION ATTRIBUTES

- Economical
- Directional fissured image

COLOR

White (WH)

VISUAL SELECTION

Edge Profile	Susp. Dwg. Pgs. 474-478 armstrongceilings.com/catdwgs	Item No.	Dimensions (Inches)	
FISSURED™ Square Lay-in				
15/16" Square Lay-in	1	**756**	24 x 24 x 5/8"	□
	1	**896**	24 x 24 x 5/8"	□
	1	**755**	24 x 48 x 5/8"	▭
	1	**895**	24 x 48 x 5/8"	▭
FISSURED Tegular				
15/16" Angled Tegular	12	**705**	24 x 24 x 5/8"	□
	12	**815**	24 x 24 x 5/8"	□

Size Capabilities		Width	Length
15/16" Square Lay-in & Tegular	Made-to-Order Sizes (4-6 Wks)	5/8" Thick	
		12" - 30"	18" - 72"

[1] Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.

PERFORMANCE SELECTION Dots represent high level of performance.

UL Classified Acoustics NRC	+ CAC	= Total Acoustics[1]	Fire Performance	Light Reflect	Mold & Mildew Protection	Sag Resist	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	Warranty
0.55	30	–	Class A	0.81	–	Std	•	Std	Std	•	1-Yr
0.55	35 •	–	Fire Guard™	0.81	–	Std	•	Std	Std	•	1-Yr
0.55	30	–	Class A	0.81	–	Std	•	Std	Std	•	1-Yr
0.55	35 •	–	Fire Guard	0.81	–	Std	•	Std	Std	•	1-Yr
0.55	30	–	Class A	0.81	–	Std	•	Std	Std	•	1-Yr
0.55	35 •	–	Fire Guard	0.81	–	Std	•	Std	Std	•	1-Yr
N/A	N/A	–	Class A	0.81	–	Std	•	Std	Std	•	1-Yr

SUSPENSION SYSTEMS

15/16"



Prelude®
Prelude® Fire Guard™

PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL labeled). Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies (Class A).

ASTM E1264 Classification
Type III, Form 2, Pattern C D
Fire Class A

Humidity/Sag Resistance
Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

VOC Emissions
GREENGUARD Gold Certified
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

GREENGUARD GOLD

Insulation Value
755, 756, 895, 896 – R Factor – 1.5 (BTU units)
R Factor – 0.26 (Watts units)
705, 815 – R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

Weight; Square Feet/Carton
705 – 0.69 lbs/SF; 64 SF/ctn
755 – 0.66 lbs/SF; 96 SF/ctn
756 – 0.67 lbs/SF; 64 SF/ctn
815 – 1.08 lbs/SF; 48 SF/ctn
895, 896 – 1.09 lbs/SF; 64 SF/ctn

Minimum Order Quantity
1 carton, excludes made-to-order panels

Metric Items Available
756M, 896M, 755M, 895M, 705M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

TechLine / 1 877 276-7876
armstrongceilings.com/commercial
(search: fissured)
BPCS-3030-718

LEED® is a registered trademark of the U.S. Green Building Council
UL is a registered trademark of UL LLC. All other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates
© 2018 AWI Licensing LLC Printed in the United States of America

Armstrong® CEILING & WALL SOLUTIONS