JA SOLAR

Harvest the Sunshine

650W

JAM72D42 LB n-type Double Glass Bifacial Modules

Premium Cells

n-Bycium+ 16BB

MBB Half-Cell Technology

26%


Up To

Cell Conversion Efficiency



Premium Modules

- Higher power generation better LCOE
- n-type with very Lower LID
- Better Temperature Coefficient
- Better low irradiance response



1% 1st-year Degradation

0.4% Annual Degradation Over 30 years

12 12-year product warranty

30 30-year linear power output warranty


Comprehensive Certificates

- IEC 61215, IEC 61730, UL 61215, UL 61730
- ISO 9001: 2015 Quality management systems
- ISO 14001: 2015 Environmental management systems
- ISO 45001: 2018 Occupational health and safety management systems
- IEC 62941: 2019 Terrestrial photovoltaic (PV) modules - Quality system for PV module manufacturing

DEEP BLUE 4.0 Pro

JAM72D42 LB n-type Double Glass Bifacial Modules

DEEP BLUE 4.0 Pro



MECHANICAL PARAMETERS

Cell	Mono
Weight	34.6kg
Dimensions	2465±2mm×1134±2mm×30±1mm
Cable Cross Section Size	4mm²(IEC), 12 AWG(UL)
No. of cells	144(6×24)
Junction Box	IP68, 3 diodes
Connector	QC 4.10-351/ MC4-EVO2A
Cable Length (Including Connector)	Portrait: 300mm(+) /400mm(-) Landscape: 1500mm(+)/1500mm(-)
Front Glass/Back Glass	2.0mm/2.0mm
Packaging Configuration	36pcs/Pallet, 576pcs/40HQ Container


Remark: customized frame color and cable length available upon request


ELECTRICAL PARAMETERS AT STC

TYPE	JAM72D42 -625/LB	JAM72D42 -630/LB	JAM72D42 -635/LB	JAM72D42 -640/LB	JAM72D42 -645/LB	JAM72D42 -650/LB
Rated Maximum Power(Pmax) [W]	625	630	635	640	645	650
Open Circuit Voltage (Voc) [V]	52.27	52.47	52.67	52.87	53.07	53.27
Maximum Power Voltage(Vmp) [V]	43.71	43.90	44.10	44.29	44.49	44.67
Short Circuit Current(Isc) [A]	15.16	15.21	15.26	15.31	15.36	15.41
Maximum Power Current(Imp) [A]	14.30	14.35	14.40	14.45	14.50	14.55
Module Efficiency [%]	22.4	22.5	22.7	22.9	23.1	23.3
Power Tolerance	0~+3%					
Temperature Coefficient of Isc(α_Isc)	+0.045%/°C					
Temperature Coefficient of Voc (β_Voc)	-0.250%/°C					
Temperature Coefficient of Pmax(γ_Pmp)	-0.290%/°C					
STC	Irradiance 1000W/m², cell temperature 25°C, AM1.5G					

Remark: Electrical data in this catalog do not refer to a single module and they are not part of the offer.
They only serve for comparison among different module types.

CHARACTERISTICS





ELECTRICAL CHARACTERISTICS WITH 10% SOLAR IRRADIATION RATIO

TYPE	JAM72D42 -625/LB	JAM72D42 -630/LB	JAM72D42 -635/LB	JAM72D42 -640/LB	JAM72D42 -645/LB	JAM72D42 -650/LB
Rated Max Power(Pmax) [W]	675	680	686	691	697	702
Open Circuit Voltage(Voc) [V]	52.27	52.47	52.67	52.87	53.07	53.27
Max Power Voltage(Vmp) [V]	43.71	43.90	44.10	44.29	44.49	44.67
Short Circuit Current(Isc) [A]	16.37	16.43	16.48	16.53	16.59	16.64
Max Power Current(Imp) [A]	15.44	15.50	15.55	15.61	15.66	15.71
Irradiation Ratio (rear/front)	10%					

* For Nextracker installations, maximum static load please take compatibility approve letter between JA Solar and Nextracker for reference.

OPERATING CONDITIONS

Maximum System Voltage	1500V DC
Operating Temperature	-40°C~+85°C
Maximum Series Fuse Rating	30A
Maximum Static Load, Front*	5400Pa(112 lb/ft²)
Maximum Static Load, Back*	2400Pa(50 lb/ft²)
NOCT	45±2°C
Bifaciality	80%±5%
Safety Class	Class II
Fire Performance	UL Type 29/Class C

JA SOLAR

Headquarters No. 8 Building, Nuode Center, No.1 Courtyard, East Auto Museum Road, Fengtai District, Beijing
Tel: +86 10 6361 1888 Fax: +86 10 6361 1999
E-mail: sales@jasolar.com marketing@jasolar.com www.jasolar.com

Specifications subject to technical changes and tests.
JA Solar reserves the right of final interpretation.

Version No. : Global-EN-20241122A