TOA

TOA INSULATOR PRIMER

Technical Data Sheet

Rev.1 10/2017

FEATURES

TOA INSULATOR PRIMER, Heat Reflecting Insulation Paint especially designed for home under harsh tropical climate.It is truly an innovation with green technology lable.It helps save the world's energy also inflammable,no added lead and mercury, totally non-toxic to all living creatures.The paint can be computerizing blened to oder via our
TOA COLORWORLD unit.Beacuse it is added 5 more benefits which comprised of :

* Heat Insulation * Waterproof * Anti Fungus
* Cover hair-line crack * Alkali resistance

It is ideal application to both exterior and interior concretes, new and old masonry surface,plasters, brick, asbestos shingles and siding

TECHNICAL INFORMATION

Type	100% Acrylic Emulsion	
Color	White Ceramic	
Film appearance	Matt	
Solid by volume	33-35	%
Solid by weight	52-54	%
Flash point	N/A	˚C
Volatile organic compounds (VOCs)	-	gram / litre
Wet film thickness	100-110	microns
Dry film thickness	40-45	microns
Theoretical coverage.	30-35	sq.meter / gallon / coat

Remark - Actual Surface coverage will depend on surface irregularities, Mixing, Application Condition method and technique; as well as the structure and dimensions of the object to be coated.

Touch dry (25-30˚C)	30	minutes
Recoat dry (25-30˚C)	4	hours
Full cure (25-30˚C)	7	days

REFERENCE STANDARD

None

APPLICATION

Tools	Roller, Brush, Spray	
Diluent	Clean Water	
Dilution (%)	0-10	% (roller and brush)
	10-20	% (spray)

The dilution could be done depends on the variation of temperature and humidit atmosphere.The given figure is the average data from actual use.

Technical Data Sheet

Rev.1 10/2017

APPLICATION SYSTEM

Surface Preparation

Old Surface

Remove to the deteriorate paint film (not use wire brush)
Areas where the fungus to kill mold polished clean with liquid TOA Microkill.Cleaning.
Then let it dry 1-2 days.
At a crack width less than 1 mm. and not break continuity.
Putty for filling with TOA acrylic acrylic filler.
Around the crack. Wider than 1 mm. or a different continuity.
Putty for filling with TOA Acrylic Sealant.

New surface

Substrate must be completely cured and dried (~1 month) free from oil, grease, mildew.

Coating system

Primer For Old Surface

Apply 1 coat of TOA CONTACT PRIMER and Apply 1 coat of TOA INSULATOR PRIMER

Primer For New Surface

Apply 1 coat of TOA INSULATOR PRIMER

Topcoat

Apply 2-3 coats of 4 seasons ,or TOA Shield-1 Nano, or Supershield

HANDLING AND STORAGE

Storage condition

: The product must be stored in accordance with national regulations.
Keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition.
Containers must be kept tightly closed.

Shelf life

: 5 years at 30-35 ^{O}C.

HEALTH AND SAFETY

: Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

: For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet.

DISCLAIMER

: The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything only the quality of the product itself. We reserve the right to change the given data without notice.

สีน้ำรองพื้นฉนวนกันร้อน ทีโอเอ

ข้อมูลทางวิชาการ

ทบทวนครั้งที่ 1 10/2560

คุณสมบัติ

เป็นสีรองพื้นปูนใหม่กันด่าง ผสมเซรามิค ป้องกันความร้อน โฟร์ซีซั่นส์ มีคุณสมบัติพิเศษดังนี้
* เป็นฉนวนป้องกันความร้อน
* ทนทานต่อด่างและคราบเกลือในปูน
* ยึดเกาะพื้นผิวดีเยี่ยม
* ป้องกันเชื้อรา

เหมาะสำหรับทาตกแต่งและป้องกันพื้นผิวปูนฉาบ คอนกรีต อิฐ กระเบื้องแผ่นเรียบทั้งภายในและภายนอก

ข้อมูลทางเทคนิค

ประเภทสี	สีน้ำทาอาคารจากเนื้ออะคริลิกแท้100%	
เฉดสี	ขาว	
ลักษณะฟิล์มสี	ชนิดด้าน	
เนื้อสีโดยปริมาตร	33-35	%
เนื้อสีโดยน้ำหนัก	52-54	%
จุดวาบไฟ	N/A	^{o}C
ปริมาณสารอินทรีย์ระเหยได้	-	กรัม ต่อ ลิตร
ความหนาฟิล์มสีเมื่อเปียก	100-110	ไมครอน
ความหนาฟิล์มสีเมื่อแห้ง	40-45	ไมครอน
การครอบคลุมพื้นที่ตามทฤษฎี	30-35	ตารางเมตร ต่อ แกลลอน ต่อ เที่ยว
	หมายเหตุ : การผสม, การใช้งาน, ความหยาบและรูพรุนของพื้นผิว มีผลต่อค่าการปกคลุมพื้นผิว	
ระยะเวลาแห้งสัมผัส (อุณหภูมิ25-30˚C)	30	นาที
ระยะเวลาแห้งทาทับ (อุณหภูมิ25-30˚C)	4	ชั่วโมง
ระยะเวลาแห้งสมบูรณ์ (อุณหภูมิ25-30˚C)	7	วัน

มาตรฐานอ้างอิง

ไม่มี

วิธีใช้งาน

อุปกรณ์	ลูกกลิ้ง แปรงทาสี เครื่องพ่น	
ตัวเจือจาง	น้ำสะอาด	
การเจือจาง (%)	0-10	% (กลิ้ง หรือ ทา)
	10-20	% (พ่น)
	อัตราส่วนดังกล่าวเป็นอัตราส่วนการเฉลี่ยจากการใช้งานจริง	
	การผสมน้ำให้ทำเมื่อต้องการปรับสภาพความข้นเหลวให้เหมาะสมกับ	
	สภาพการใช้งานตามสภาพอุณหภูมิอากาศและความชื้นสัมพัทธ์	

ระบบการใช้งาน

การเตรียมพื้นผิว

พื้นผิวเก่า

ขัดล้างสีเดิมที่เสื่อมสภาพออกให้หมด (ไม่ควรใช้แปรงลวด)
บริเวณที่มีเชื้อราหรือตะไคร่น้ำขัดล้างด้วยน้ำยาฆ่าเชื้อรา TOA Microkill
*ถ้ามีรอยแตกร้าวให้ทำเหมือนพื้นผิวใหม่

พื้นผิวใหม่

ทำความสะอาดผนังให้ปราศจากเศษฝุ่นผง เศษซีเมนต์ และคราบไข
บริเวณที่มีรอยแตกร้าวความกว้างน้อยกว่า 1 มิลลิเมตรและไม่แตกต่อเนื่อง
ให้อุดโป๊วด้วยทีโอเอ อะครีลิค ฟิลเลอร์
บริเวณที่มีรอยแตกร้าว ความกว้างมากกว่า 1 มิลลิเมตรหรือมีการแตกต่อเนื่อง
ให้อุดโป๊วด้วย ทีโอเอ อะครีลิค ซิลแลนท์

ข้อมูลทางวิชาการ

ทบทวนครั้งที่ 1 10/2560

ระบบการทาสี

สีรองพื้นสำหรับพื้นผิวเก่า	ทาน้ำยารองพื้นปูนทับสีเก่า ทีโอเอ คอนแทค ไพรเมอร์ จำนวน 1 เที่ยวและ ทาสีน้ำรองพื้นฉนวนกันร้อน ทีโอเอ จำนวน 1 เที่ยว
สีรองพื้นสำหรับพื้นผิวใหม่	ทาสีน้ำรองพื้นฉนวนกันร้อน ทีโอเอ จำนวน 1 เที่ยว
สีทับหน้า	ทาสีทับหน้า ตั้งแต่กลุ่มผลิตภัณฑ์ โฟร์ซีซั่น , ทีโอเอ ชิลด์ วัน นาโน , ซุปเปอร์ชิลด์ จำนวน 2-3 เที่ยว

การเก็บรักษา

สภาวะการเก็บรักษา	: จัดเก็บสินค้าในที่แห้ง มีอากาศถ่ายเทดี ปิดฝาให้สนิท ให้แน่นตลอดเวลา ไม่ควรเก็บในที่ร้อนและไม่ให้ถูกแสงแดดโดยตรง
อายุผลิตภัณฑ์	: 5 ปี ที่อุณหภูมิ 30-35 องศาเซลเซียส

ข้อมูลสุขภาพและความปลอดภัย

: กรุณาดูข้อควรระวังที่ติดไว้บนภาชนะบรรจุ การทำงานสีควรทำในที่ที่อากาศถ่ายเทสะดวก ควรใส่หน้ากากเมื่อทำการพ่นสีและพยายามเลี่ยงมิให้สัมผัสผิวหนัง หรือสูดดม ถ้าสีหกใส่ผิวหนังควรล้างด้วยน้ำสะอาดกับสบู่ทันที ถ้าสีเข้าตาควรล้างด้วยน้ำสะอาดทันทีและรีบไปพบแพทย์

: รายละเอียดด้านความปลอดภัยเกี่ยวกับการใช้ผลิตภัณฑ์ ระบุไว้ในข้อมูลด้านความปลอดภัย

การสงวนสิทธิ์เรียกร้อง

: รายละเอียดข้างบนนี้ได้มาโดยการทดลอง และจากประสบการณ์ที่ผ่านมา เนื่องจากสีถูกนำไปใช้ในสภาวะแตกต่างกันเราจึงไม่สามารถรับประกันในสิ่งอื่นใดนอกจากคุณภาพของสีเท่านั้น **บริษัทขอสงวนสิทธิ์ที่จะเปลี่ยนแปลงข้อมูลโดยมิต้องแจ้งล่วงหน้า**